

SCR3311

Premium USB Solution - One-hand operation



Overview

The SCR3311 continues the line of SCM Microsystems' market leading smart card reader products using STCII chip and leveraging proven and industry indorsed SCM's technology. It also offers a one-hand operation with different weight options. The SCR3311 includes support for USB CCID, PC/SC, EMV and all other relevant security standards. Together, these features enable high performance, cost effective solutions to secure logical access. User-friendly and elegant, the SCR3311 offers the best price/performance ratio in the market.

SCR3311 Benefits

- On-board flash for seamless firmware upgrades in the field prevents obsolescence
- EMV 2000 Level 1 and PC/SC certification in a single solution
- · One-hand operation with different weight options
- High performance
- Fully tested and compliant with all major smart cards in the market
- · Customizing options: casing, colors, and company logo

PC Security Solutions

U.S. Headquarters SCM Microsystems Inc. 466 Kato Terrace Fremont, CA 94539 USA E-mail scmsales@scmmicro.com Phone +1 510 360 2300 Fax +1 510 360 0211

European Headquarters SCM Microsystems GmbH Oskar-Messter-Str. 13 D-85737 Ismaning, Germany E-mail sales@scmmicro.de Phone +49 89 9595 5000 Fax +49 89 9595 5555

SCM Microsystems Japan, Inc. 8F Hirakawacho Ronstate, 2-11-1, Hirakawa-cho, Chiyoda-ku, Tokyo, Japan 102-0093 E-mail sales@scmmicro.co.jp Phone +81 3 3511 8511 Fax +81 3 3511 8516

SCM Microsystems France ZE Athélia II 216, avenue du Serpolet 13704 La Ciotat Cedex - France E-mail sales@scmmicro.fr Phone +33 442 838 000 Fax +33 442 838 001

SCM Microsystems (Asia) Pte. Ltd. 25 Serangoon North Ave 5 #06-00 Keppel Digihub Singapore 554914 E-mail sales@scmmicro.com.sg Phone +65 6551 5233 Fax +65 6483 0210

SCM Microsystems India Pvt. Ltd. Module No. 0506, 0507 & 0508 D' Block South, 5th Floor Tidel Park, 4 Canal Bank Road Taramani Chennai 600113, India E-mail sales@scmmicro.co.in Phone +91 44 2254 0020 Fax +91 44 2254 0029















www.scmmicro.com



SCR3311

Technical Data

Host Interface	Full speed USB (12 Mbps)Bus powered deviceCCID compliant
Smart Card Interface	 T=0, T=1 protocol support Memory card support through SCM MCARD API Communication speed up to 344,105 bps (PPS, FI parameter) Frequency up to 12 MHz (PPS, DI parameter) Support ISO 7816 Class A and AB smart card
Smart Card Connector	8 contacts - ISO location100,000 insertionsSliding contact
Human Interface	One dual state green LED
Cable/Power	Cable: 2m long with USB type A connector Power through USB bus
Dimensions	• LWH 95 x 64 x 85 mm
Weight	Two options • Heavy weight - approx. 420 g • Light - approx. 150 g
Operating Temperature	o° to 50° Celsius
OS	 Windows® 98, ME, 2000, XP, Server 2003 Windows® CE 4.2, 5.0 MacOS X, Linux, Solaris
API	PC/SCCT-API (thru wrapper on top of PC/SC)
Approvals	FCC Class B part 15, cULus, CE USB Microsoft® WHQL 2000, XP, Server2003 EMV 2000 Level 1

Technical data are subject to change without notice.

The SCM Microsystems' Advantage

SCM Microsystems brings over a decade of experience in ASIC and smart card reader development to this unique product. With its dedicated Research and Development team and a true global presence, SCM Microsystems delivers high quality products catering to the various requirements in the security field. SCM offers customization of products to suit application needs.

Typical advantages of an SCM Microsystems product include:

- More than 80 patents
- · High quality mass production capability
- Industry endorsed SmartOS™ middleware
- · Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and smart card industry leaders
- Direct significant long-term relationships with all leading smart card manufacturers and application providers

