

ExpressCard 54 - SCR3340

Next Generation PC Card Technology



Overview

SCM's new SCR3340 ExpressCard[™] reader represents the next generation of PC Card technology. Based on SCM's STC II smart card interface chip, the SCR3340 leverages existing and already qualified hardware and software, making it easy for OEMs to qualify and integrate the readers.

The ExpressCard standard gives users a very easy way to add hardware or media to notebooks, desktops or other compliant systems.

The readers are designed to meet the requirements of the ExpressCard interface specification, developed by a large number of PCMCIA member companies including technology leaders, system manufacturers, card manufacturers, and representatives from the PC Card industry.

SCR3340 Benefits

- · Firmware field upgrades to prevent obsolescence
- · A smaller and faster PC Card solution
- · Suitable for both mobile and desktop systems
- · USB 2.0 full speed and CCID, compliant leveraging existing and proven technology
- · Lower system and card complexity
- · A very easy way to add hardware or media to the system







PC Security Solutions

U.S. Headquarters SCM Microsystems Inc. 466 Kato Terrace Fremont, CA 94539 USA E-mail scmsales@scmmicro.com Phone +1 510 360 2300 Fax +1 510 360 0211

European Headquarters SCM Microsystems GmbH Oskar-Messter-Str. 13 D-85737 Ismaning, Germany E-mail sales@scmmicro.de Phone +49 89 9595 5000 Fax +49 89 9595 5555

SCM Microsystems Japan, Inc. 8F Hirakawacho Ronstate, 2-11-1, Hirakawa-cho, Chiyoda-ku, Tokyo, Japan 102-0093 E-mail sales@scmmicro.co.jp Phone +81 3 3511 8511 Fax +81 3 3511 8516

SCM Microsystems France ZE Athélia II 216, avenue du Serpolet 13704 La Ciotat Cedex - France E-mail sales@scmmicro.fr Phone +33 442 838 000 Fax +33 442 838 001

SCM Microsystems (Asia) Pte. Ltd. 25 Serangoon North Ave 5 #06-00 Keppel Digihub Singapore 554914 E-mail sales@scmmicro.com.sg Phone +65 6451 5233 Fax +65 6483 0210

SCM Microsystems India Pvt. Ltd. Module No. 0506, 0507 & 0508 D' Block South, 5th Floor Tidel Park, 4 Canal Bank Road Taramani Chennai 600113, India E-mail sales@scmmicro.co.in Phone +91 44 2254 0029 Fax +91 44 2254 0029

www.scmmicro.com



ExpressCard 54 - SCR3340

Technical Data

Host Interface	• ExpressCard 54 • Full speed USB (12 Mbps) • CCID compliant
Smart Card Interface	 T=0, T=1 protocol support Memory card support through SCM MCard API Communication speed up to 344,105 bps (DI) Frequency up to 12 MHz (FI) Support ISO 7816-3 Class A and AB smart card
Smart Card Connector	 8 contacts - ISO location approx. 100,000 insertions Sliding contact
Dimensions	• ExpressCard 54 (LWH 75x54x5), weight 25 grams
Operating Temperature	0° to 55° Celsius, 95% humidity non-condensing
OS	Windows® XP, Server2003 (32 and 64 bits)
API	PC/SCCT-API (thru wrapper on top of PC/SC)
Approvals	FCC Class B part 15, UL, CE, VCCI Microsoft® WHQL 2000, XP, Server2003 ExpressCard EMV 2000 Level 1

Technical data are subject to change without notice.

Availability

- Samples 09/2005
- Production 12/2005

The SCM Microsystems' Advantage

SCM Microsystems brings over a decade of experience in ASIC and smart card reader development to this unique product. With its dedicated Research and Development team and a true global presence, SCM Microsystems delivers high quality products catering to the various requirements in the security field. SCM offers customization of products to suit application needs.

Typical advantages of an SCM Microsystems product include:

- · More than 80 patents
- High quality mass production capability
- Industry endorsed SmartOS[™] middleware
- · Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and smart card industry leaders
- Direct significant long-term relationships with all leading smart card manufacturers and application providers



ALL INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED "AS IS"; SCM ASSUMES NO RESPONSIBILITY FOR ITS ACCURACY AND/OR COMPLETENESS. © SCM Microsystems Inc., 2005 0819 all rights reserved. SCM and SCM Microsystems are trademarks of SCM Microsystems Inc. All other trademarks are trademarks of their respective owners. In no event will SCM Microsystems Inc. be liable for damages arising directly or indirectly form any use of the information contained in this document. The SCM Microsystems Inc. homepage can be found at www.scmmicro.com